ROYPOW TECHNOLOGY CO., LTD. has a policy of improving products continuously. All the information in this catalogue is provided for reference only. We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice. Trademarks are the property of ROYPOW TECHNOLOGY CO., LTD. or their respective owners. Technical data and illustrations are not binding. We assume no liability for misprints.

Version: February 26, 2025, LiFePO4 Batteries for Airport Ground Support Equipment



## **Global Lithium+ Solution Provider**

# **LiFePO4 Batteries for** Airport Ground Support Equipment and Ground Power Units



#### **ROYPOW Technology Co., Ltd.**

Tel: +86 (0)752-327 9099

Email: sales@roypow.com service@roypow.com marketing@roypow.com

Web: www.roypow.com

Add: ROYPOW Industrial Park, No. 16, Dongsheng South Road, Chenjiang Street, Zhongkai High-Tech District, Huizhou City, Guangdong Province, China

#### ROYPOW (USA) Technology Co., Ltd.

Tel: +1 512 688 5555 (Texas Office) Email: sales@roypowusa.com Email: service@roypowusa.com

Web: www.roypow.com

Head Office: 5901 Triumph St, Commerce, CA 90040, USA Texas Office: 2350 Campbell Creek Blvd #100 Richardson, TX 75082, USA Florida Office: 277 Douglas Avenue, Unit 1004, Altamonte Springs, FL 32714, USA Indiana Office: 5545 W Raymond St, Ste H Indianapolis, IN 46241, USA Georgia Office: 1150 Cobb International PI NW Ste E, Kennesaw, GA 30152, USA

#### **ROYPOW Technology UK Limited**

Tel: +44 (0) 7918 955 940 Email: sales.uk@roypow.com Add: Regus Green Park, 200 Brook Dr, Reading RG2 6UB, UK

## **ROYPOW Battery Technology (Pty) Ltd**

Email: sales.za@roypow.com Tel: +27 69 89 55555 Add: 53 Lake Rd, Longmeadow Business Estate, Edenvale, 1609, South Africa

#### ROYPOW (Europe) Technology B.V.

Email: sales.eu@roypow.com Tel: +31 702 001 114 Web: www.roypoweurope.com Add: K.P. van der Mandelelaan 84, 3062 MB Rotterdam, The Netherlands

#### **ROYPOW Australia Technology Pty Ltd**

Email: sales@roypowtech.com.au Tel: +61 29185 0814 Web: www.roypowtech.com.au Add: Suite 803a, 18 Orion Road, Lane Cove, NSW, 2066, Australia

#### **ROYPOW Technology GmbH**

Tel: +49 (0) 176 2358 8956 Email: sales.de@roypow.com Web: www.rovpow.ambh Add: Rosa-Parks-Straße 4, 64295 Darmstadt, Germany

#### ROYPOW株式会社

Tel: +81 090 7092 6969 Email: info@roypow.co.jp Web: www.roypow.co.jp Add: 〒271-0094 千葉県松戸市上矢切299-7

#### ROYPOW Technology Co., Ltd (Korea)

Tel:1555-2016 Email: sales.kr@roypow.com Add: 2405, GIDC Gwangmyeong station A Dong, 43 Iljik-ro, Gwangmyeong-si, Gyeonggi-do, Korea









▶ sales@rovpow.com www.roypow.com



# ROYPOW For One-stop New Energy Solutions

- R&D, manufacturing and sales of motive power systems and energy storage systems as one-stop solutions
- Fully automatic production lines, a full range of test equipment and an advanced MES
- · Covering Low-Speed Vehicles' Batteries, Industrial Batteries, as well as Residential ESS, Commercial & Industrial ESS, and Mobile ESS
- Self-development of power electronics technologies, including PCS, BMS, and EMS



## Quality Control Certificates:

- Environmental Management System: ISO 14001:2015
- Occupational Health and  $\checkmark$ Safety Management System: ISO45001:2018
- ✓ Quality Management System: ISO 9001:2015, IATF16949:2016

| Product Certifications:

Management System: ISO/IEC 27001:2022 ✓ Social Accountability

Information Security

- Management System: SA8000:2014
- ✓ Hazardous Substance Process Management: IECQ QC 080000





EN 62477, EN 62040, (EU) 2023/1542, EN 62109-1. EN 62109-2



## R&D and Manufacturing Highlights

As a result of these investments, ROYPOW is capable of "end-to-end" integrated delivery, making our products out-perform the industry norms.



BMS, PCS, EMS All Designed in House

## Global Sales and Service Network



Timely Delivery

ROYPOW has comprehensively unfolded its overseas market layout to ensure the localization of R&D, manufacturing, marketing and service, becoming one of your most reliable and valuable partners.



## Upgrading to New Technology, with Our Turnkey Solutions.

With years of dedication to new energy solutions, we are proud to offer customers professional solutions for:

- > Low-speed Vehicle Batteries
- > Battery Systems for Off-highway Applications
- Residential Energy Storage Systems
- > Mobile Energy Storage Systems







Advanced MES System

Hassle-free After-sales Service



Fast Response **Technical Support** 

- > Industrial Batteries
- > Battery Systems for Emerging Applications
- Commercial & Industrial Energy Storage Systems
- Motors, Controllers and Chargers

Introduction of ROYPOW LiFePO<sub>4</sub> GSE Batteries

# Ideal **Power Solution** for GSE Operations

Electric ground support equipment is the foundation of a functional airport. Serving in any weather condition for efficient ground handling from the tarmac to the terminal demands the reliability of the power source.

technologies offer significant advantages compared to conventional GSE powered by Internal Combustion (IC) engines or lead acid, making them a worthwhile investment and a smart long-term solution.

# Switch From IC Engines and Lead Acid to ROYPOW Lithium for GSE



- Meet the regulations for reduced carbon footprint
- Low engine noise on the ramp
- Fewer moving parts that require maintenance
- Reduced fuel consumption and costs
- Lower safety and health risks for ground personnel





Converting to lithium-powered GSE may require a higher initial investment, **but its ongoing** savings can give you a more cost-effective bill.



- ✓ One battery for multiple shifts
- Eliminate battery maintenance labor cost
- Charge more quickly for maximized uptime and increased equipment availability
- Stable voltage at all levels of discharge
- No dangerous substances or spillage



- Long service life without frequent battery swaps
- Perform better in cooler and hotter environments

## Designed to Last, Engineered to Perform



Speed and efficiency are essential in ground support equipment to minimize the turnaround time. ROYPOW LiFePO4 batteries, from internal to external, are manufactured to the highest standards of durability, reliability, and safety for the best on-time GSE operations.

## Rugged & Automotive-Grade, Longer Lifespan as It Can Be



The LiFePO4 GSE batteries are built with advanced steel casing and watertight enclosures to make them tough enough and up to the challenges of harsh working conditions such as vibrations, impacts, or water ingress experienced on airport ground handling.

Vibration-Resistant

✓ Shock-Resistant

IP65-Rated Protection

## Built-in Fire Extinguisher



Each battery is equipped with one or more specially designed fire extinguisher devices. Once the battery exceeds the temperature limit and has the potential to fire, the device will activate automatically for fire protection.

Fire-resistant materials adopted between battery modules double the guarantee for fire safety.

With 10 years of battery life and can withstand up to 3,500 cycles.

Long Life

## **Consistent Power**

No voltage drop at the end of the cycle. Stable in extreme tempertures.

#### Zero Maintenance

Eliminate the need for frequent battery swaps or maintenance.



## Fast & Opportunity Charge

Ensure increased equipment uptime and more flexibility for GSE schedules without worrying about unexpected unavailability.

t)

 $\odot$ 

 $(\mathbf{X})$ 

 $\odot$ 

## **Optional Heating Function**

Heat the battery for optimal charging in colder seasons to keep things moving for airports.

## **5-Year Warranty**

5 years of warranty brings you hassle-free experience.

Compatible with Most GSE Applications

# **Battery Management** System (BMS)

The built-in BMS is equipped with automotive-grade components assuring safety, top quality and high energy density to provide a fully optimized solution for demanding industrial applications.

BMS software ensures the battery provides peak performance when in operation, delivers longer run time between charges, maximizes the total battery lifespan and to communicate well between the charger, battery and users. (BMS programmable based on customer's tech protocol)

## The BMS can offer:

## All-time Cell Balancing and Battery Management.

Through the intelligent balancing strategy, balancing between individual cells can be realized. The BMS can keep the battery's consistency at all times when in operation, maximizing the battery efficiency and improving the battery's working life.

#### **Battery Real-time Monitoring and Communication Through CAN.**

Monitoring cell voltage, electric current and battery temperature so that any movement outside the normal range disconnects the cell or the entire battery.

## Fault Alarm and Safety Protection.

When the battery is less than 10%, it will beep to prompt for charging in case of stopping somewhere far away from the charge station suddenly without notice. Over/under voltage, low/over temperature, over current or other faults will prompt to make the battery safe. Safety always comes first.



**BMS** 



**4G Module** 

**Fast Charger** (IP54 Protection)



ROYPOW smart 4G module can realize remote monitoring in real time, even in different countries. If some faults occur, you can get an alarm in time. Once the faults can not be solved, you can get a remote diagnosis online from us to solve the problems as soon as possible.

chargers.)

✓ Safe & Fast Charging Charge safely and quickly for increased equipment availability between flights.

Zero Maintenance Highly waterproof and vibration-resistant design ensures stable charging and requires virtually no maintenance.

# Intelligent, Safe & Reliable

# Smart 4G Module

- Remote Software Upgrades
- Easy Network Connection
- GPS Location
- More Customized Functions

# **Chargers for LiFePO4 GSE Batteries**

Charge with ROYPOW chargers to deliver a fast charging experience, keep the best communication between the batteries and chargers, and ensure optimal battery performance for extended battery life. (ROYPOW GSE batteries are compatible with Delta-Q and ZIVAN

## Intelligent Protection

Built-in multiple charging protections and advanced technologies ensure reliable performance.

Applications





Standard and Customizable Battery Systems for **GSE** Applications









## Specifications

Technical Specifications						Charge/ Discharge Current		General			
Model	Nominal Voltage	Working Voltage Range	Rated Capacity	Rated Energy	Life Cycles	Dimensions (L*W*H)	Weight Ibs. (kg)	Charge Current	Discharge Current	Casing Material	IP Rating
48 V Syste	em										
TR48280D-A	51.2 V	40~58.4 V	280 Ah	14.34 kWh	>3,500 Times	32.09 x 29.13 x 18.7 inch (815 x 740 x 475 mm)	1499.14±55.12 lbs. (680±25 kg)	145 A	350 A	Steel	IP65
TR48460K		41.6~58.4 V	460 Ah	23.55 kWh		32.68 x 24.8 x 24.69 inch (830 x 630 x 627 mm)	1884.95±110.23 lbs. (855±50 kg)	235 A	320 A		IP65
80 V Syste	em										
TR80230	80 V	67.2 V-87.6 V	230 Ah	17.66 kwh	>3,500 Times	38.19 x 21.65 x 10.63 inch (970 x 550 x 270mm)	392.42 lbs. (178kg)	100 A	200 A		IP65
TR80314		67.2 V-87.6 V	314 Ah	24.11 kwh		44.09 x 9.84 x 22.52 inch (1120 x 250 x 572mm)	546.75 lbs. (248kg)	100 A	200 A		IP65
TR80460		67.2 V-87.6 V	460 Ah	35.32 kwh		38.19 x 21.65 x 22.44 inch (970 x 550 x 570mm)	749.57 lbs. (340kg)	200 A	350 A	Steel	IP65
TR80628		67.2 V-87.6 V	628 Ah	48.23 kwh		44.09 x 17.32 x 22.52 inch (1120 x 440 x 572mm)	954.6 lbs. (433kg)	200 A	350 A		IP65
Working			Char	ge		Discharge		S	Storage (1 m	ionth )	

Temperature Range

-4°F~131°F ( -20°C ~ 55°C)

1. All pictures shown are for reference only and data are based on ROYPOW standard test procedures. 2. Actual performance may vary according to local conditions. Only authorized personnel are allowed to operate or make adjustments to the batteries. 3.We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice.

-4°F~131°F ( -20°C ~ 55°C)

-4°F~131°F ( -20°C ~ 55°C)

# 537V / 280Ah **High-Voltage LiFePO4 Batteries** for Ground Power Units (GPU)

WD5YD5







Compatible with ROYPOW charger for optimal performance and extended life.



Equipped with UL94 V-0-rated fire-retardant materials to offer advanced protection for enhanced safety.

## Specifications

High-voltage Solution
Single Battery Pack
Voltage / Capacity (Single Pack)
System Voltage
System Capacity
Continuous Charge / Discharge Current
Instantaneous Charge and Discharge Current
Cooling Method
IP Rating

1. All pictures shown are for reference only and data are based on ROYPOW standard test procedures. 2. Actual performance may vary according to local conditions. Only authorized personnel are allowed to operate or make adjustments to the batteries. 3.We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice.

## Applications:





Tow Tractor Bag/ Tow/Cargo Trailer





LAV Service/ Water Service Truck

Aircraft Pushback Tractor

Aircraft Towbarless Tractor





Designed to handle high currents, delivering robust power output for demanding ground handling.



Optional liquid-cooling function to optimize battery performance and battery lifetime.



Intelligent thermal runaway management with fire suppression and spread prevention to minimize the risk of fire hazards.

1C-rate

51.2 V / 304 Ah or 51.2 V / 280 Ah

256 - 870.4 V

32.7 - 2785.2 kWh

Discharge / Charge: 0.35C / 100 A

Discharge / Charge: 1C / 280 A, 30 s

Air Cooled or Liquid Cooled

IP67









Cargo Loader

Passenger Stairs



Container/ Pallet Transporter

# **Onboard Chargers for 80V GSE Batteries**

Maximize Uptime with Safe, Efficient Charging Solutions

## Features



IP65 ingress rating

Safe in different environment/weather conditions



#### **Multiple Safety Protections**

Protection against burnout, reverse connection of batteries, no load, and short circuit as well as automatic shutdown when fully charged

## Specifications

Model	
Phase	Thre
Rated Voltage for Battery Pack	
AC Input Voltage	Line V
Max. Output Voltage	
AC Input Max. Current	
Max. Output Current	
Protection Level	
Dimension (L x W x H)	
Net Weight	

1. All pictures shown are for reference only and data are based on ROYPOW standard test procedures. 2. Actual performance may vary according to local conditions. Only authorized personnel are allowed to operate or make adjustments to the chargers. 3.We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice.



## Well-proven reliability

Robust and durable designs for the shell and active cooling fan



## Intelligent Control

Built-in Bluetooth with Apps control to configure parameters and charging curves easily

## WT8050

e-phase Three-wire + PE Line

80V

oltage 260~457VAC; 50Hz/60Hz

113V

9A@380VAC

50A

IP65

419 x 281.5 x 143 mm

18 kg