

ROYPOW TECHNOLOGY CO., LTD. has a policy of improving products continuously. All the information in this catalogue is provided for reference only. We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice. Trademarks are the property of ROYPOW TECHNOLOGY CO., LTD. or their respective owners. Technical data and illustrations are not binding. We assume no liability for misprints.

Version: March 05, 2025, LiFePO₄ Batteries for Industrial Applications



LiFePO₄ Batteries for Industrial Applications

Drop-In Lithium-Ion
Replacement for
Lead Acid Batteries



ROYPOW Technology Co., Ltd.

Tel: +86 (0)752-327 9099

Email: sales@roypow.com
service@roypow.com
marketing@roypow.com

Web: www.roypow.com

Add: ROYPOW Industrial Park, No.16, Dongsheng South Road, Chenjiang Street, Zhongkai High-Tech District, Huizhou City, Guangdong Province, China

ROYPOW (USA) Technology Co., Ltd.

Tel: +1 512 688 5555 (Texas Office)

Email: sales@roypowusa.com
service@roypowusa.com

Web: www.roypow.com

Head Office: 5901 Triumph St, Commerce, CA 90040, USA

Texas Office: 2350 Campbell Creek Blvd #100 Richardson, TX 75082, USA

Florida Office: 277 Douglas Avenue, Unit 1004, Altamonte Springs, FL 32714, USA

Indiana Office: 5545 W Raymond St, Ste H Indianapolis, IN 46241, USA

Georgia Office: 1150 Cobb International PI NW Ste A, Kennesaw, GA 30152, USA

ROYPOW Technology UK Limited

Tel: +44 (0) 7918 955 940

Email: sales.uk@roypow.com

Add: Regus Green Park, 200 Brook Dr, Reading RG2 6UB, UK

ROYPOW Battery Technology (Pty) Ltd

Email: sales.za@roypow.com

Tel: +27 69 89 55555

Add: 53 Lake Rd, Longmeadow Business Estate, Edenvale, 1609, South Africa

ROYPOW (Europe) Technology B.V.

Email: sales.eu@roypow.com

Tel: +31 702 001 114

Web: www.roypoweurope.com

Add: K.P. van der Mandelelaan 84, 3062 MB Rotterdam, The Netherlands

ROYPOW Australia Technology Pty Ltd

Email: sales@roypowtech.com.au

Tel: +61 29185 0814

Web: www.roypowtech.com.au

Add: Suite 803a, 18 Orion Road, Lane Cove, NSW, 2066, Australia

ROYPOW Technology GmbH

Tel: +49 (0) 176 2358 8956

Email: sales.de@roypow.com

Web: www.roypow.gmbh

Add: Rosa-Parks-Straße 4, 64295 Darmstadt, Germany

ROYPOW株式会社

Tel: +81 090 7092 6969

Email: info@roypow.co.jp

Web: www.roypow.co.jp

Add: 〒271-0094 千葉県松戸市上矢切299-7

ROYPOW Technology Co., Ltd (Korea)

Tel: 1555-2016

Email: sales.kr@roypow.com

Add: 2405, GIDC Gwangmyeong station A Dong, 43 Iljik-ro, Gwangmyeong-si, Gyeonggi-do, Korea

Forklifts:

Toyota Hyster Crown

Clark Hyundai YALE

Linde Doosan Jungheinrich

AWPs:

JLG MEC CTE

SKYJACK Genie

Snorkel Mantall

Cleaning Equipment:

Tennant Nilfisk Karcher Hako

Clarke IPC ICE NSS Betco

Minuteman PowerBoss Eureka



sales@roypow.com

www.roypow.com



Scan it!



*ROYPOW,
Your Trusted Partner*

Contents

About Us

LiFePO₄ Batteries for AGVs and AMRs

LiFePO₄ Batteries for Forklifts

LiFePO₄ Batteries for Aerial Work Platforms

LiFePO₄ Batteries for Floor Cleaning Machines



ROYPOW

For One-stop New Energy Solutions

- R&D, manufacturing and sales of motive power systems and energy storage systems as one-stop solutions
- Fully automatic production lines, a full range of test equipment and an advanced MES
- Covering Low-Speed Vehicles' Batteries, Industrial Batteries, as well as Residential ESS, Commercial & Industrial ESS, and Mobile ESS
- Self-development of power electronics technologies, including PCS, BMS, and EMS



750+ Employees
190+ R&D People
105,000 m² Headquarters Floor Area
2,500 m² Testing Center
231 Patents

Quality Control Certificates:

- ✓ Environmental Management System: ISO 14001:2015
- ✓ Occupational Health and Safety Management System: ISO 45001:2018
- ✓ Quality Management System: ISO 9001:2015, IATF16949:2016
- ✓ Information Security Management System: ISO/IEC 27001:2022
- ✓ Social Accountability Management System: SA8000:2014
- ✓ Hazardous Substance Process Management: IECQ QC 080000



Product Certifications:

UL 1973, UL 9540A, UL 9540, UL 2580, UL 2271, UL 1741
 IEC 62619
 EN 62477, EN 62040, (EU) 2023/1542, EN 62109-1, EN 62109-2

UL **EMC** **FCC, IEC/EN 61000-6, BS EN IEC 61000-6**
IEEE 1547 **Function Safety** **IEC 60730, ISO 13849-1**
CB **Transport** **UN 38.3**
CE **RoHS** **RoHS Directive 2011/65/EU & (EU) 2015/863**

R&D and Manufacturing Highlights


As a result of these investments, ROYPOW is capable of "end-to-end" integrated delivery, making our products out-perform the industry norms.

- Fully Automatic Production Lines
- BMS, PCS, EMS All Designed in House
- All-round Testing
- Advanced MES System

Global Sales and Service Network

- Timely Delivery
- Hassle-free After-sales Service
- Fast Response Technical Support

ROYPOW has comprehensively unfolded its overseas market layout to ensure the localization of R&D, manufacturing, marketing and service, becoming one of your most reliable and valuable partners.



Upgrading to New Technology, with Our Turnkey Solutions.

With years of dedication to new energy solutions, we are proud to offer customers professional solutions for:

- Low-speed Vehicle Batteries
- Battery Systems for Off-highway Applications
- Residential Energy Storage Systems
- Mobile Energy Storage Systems
- Industrial Batteries
- Battery Systems for Emerging Applications
- Commercial & Industrial Energy Storage Systems
- Motors, Controllers and Chargers



New Technology. Create Great Value for Your Business

Converting from lead-acid to lithium-ion is easy and cost-effective and increases the productivity of the fleets and the operator.




Benefits of Lithium-ion Batteries

Lead-acid	LiFePO ₄ battery		
 3 years design life	 up to 10 years design life	Longer life 3 to 4 times lead-acid lifespan	<ul style="list-style-type: none"> ✓ Reduces overall battery investment ✓ Eco-friendly ✓ Minimize the need for spares
 Frequent maintenance	 No maintenance	0 maintenance no need for regular filling of distilled water and electrolyte	<ul style="list-style-type: none"> ✓ No regular filling of distilled water ✓ Saving costs on labor and maintenance ✓ Less unplanned downtime and improved productivity ✓ No frequent battery replacements
 1-2 years warranty	 5 years warranty	Extended warranty bring you peace of mind	<ul style="list-style-type: none"> ✓ Durable and reliable ✓ Reduces maintenance and labor costs ✓ Quality guarantee

Reduce Downtime, Increase Equipment Availability

In day-to-day operations, the battery can be charged even during short breaks, such as taking a rest or changing shifts, effectively increasing productivity.

- ✓ Reduces the need for a full charge every time.
- ✓ Eliminates the need for frequent time-consuming battery swaps.
- ✓ Eliminates the risk of battery-changing accidents.
- ✓ Opportunity charge during breaks, lunch and at shift changes. Charge anytime equipment is not in use.



Rapid Charging

Whether you have a single-shift or a large fleet working 24/7, fast charge is one of the most important advantages.



TIPS


Why choose LiFePO₄ batteries for industrial applications?

There are a few lithium-ion chemistries to choose from. ROYPOW uses LFP or Lithium Iron Phosphate, one of the most thermally stable and safe lithium-ion chemistries for industrial applications.

LFP offers longer life, is more energy-dense, more stable, is more compact, and weighs less than lead-acid. Our battery packs are sealed units requiring no daily or weekly watering and no maintenance. LFP is ideal for batteries used in industrial applications.

Consistent Power

Lithium-ion batteries deliver consistently high performance, which maintains greater productivity even toward the end of a shift.



Eliminate the Need for a Dedicated Charging Area and Frequent Battery Swaps

- ✓ Minimize the need to buy, store and maintain spares.
- ✓ Eliminate the cost and storage space required for additional lead-acid batteries.
- ✓ No gassing, no ventilation system needed when charging. No hazardous acid spills.



Small Investment, Big Return



Converting your battery to lithium-ion may require a higher initial investment, but its ongoing savings on energy, equipment, labor and downtime will dramatically lower your total cost of ownership (TCO).



The LiFePO₄ batteries can offer you...

- ✓ Longer life reduces overall battery investment.
- ✓ No maintenance saves labor and maintenance costs.
- ✓ No gas or acid spills, avoids the space, equipment and running costs of a battery room and ventilation system.
- ✓ Energy saving and less downtime, improve productivity.

5-year Cost Comparison to Increase Your Overall Return on Investments.

Save Up to **70%** Expenses in 5 Years

Below is the 5-year expenditure table comparing ROYPOW LiFePO₄ batteries with lead-acid batteries.

Purchases over 5 Years	Lead-acid Battery	LiFePO ₄ Battery
Battery cost	5 stacks of coins	1 stack of coins
Maintenance	5 stacks of coins	/
Electricity waste	5 stacks of coins	/
Installation	5 stacks of coins	1 stack of coins
Shipping	5 stacks of coins	1 stack of coins

Remark: Actual costs may vary according to local conditions.

ROYPOW Batteries with Smart & Integrated Systems

Provide exceptional performance to get the job done and improve your productivity, which means fewer hours of unplanned downtime and more productive hours on your work.


0 Maintenance
Up to **3,500+** Cycle Life

5 yr Warranty
Up to **10** yr Design Life



Durable

ROYPOW batteries have an IP65 ingress rating. They will provide fast lifting and travel speeds at all levels of discharge, under all-weather working conditions.



4G Modules (for Forklift Batteries)

4G modules are for remote monitoring of the battery SOC, temperature, as well as diagnosis and remote software upgrades. Solve software problems in real time.

Built-in Protection

Intelligent BMS is for automatic cell balancing and advanced battery management. The LiFePO₄ batteries have greater thermal and chemical stability.

For AGVs and AMRs

Durable, stable, and safe. Suitable for various operation applications and improve working efficiency.




For Forklifts

Specially designed, smart, cost-effective. Ideal for multi-shift operations.



For Aerial Work Platforms

High consistent performance and maintenance free for safe and easy aerial work.



For Floor Cleaning Machines

Hassle-free, cost-effective, and good for you and the planet.



Automotive-grade Battery Manufacturing

To build a world-renowned lithium-ion battery brand and provide better solutions for you.



LiFePO₄ Batteries for AGVs and AMRs

Always sufficient power for your AGVs and AMRs.

Pairing your AGVs and AMRs with ROYPOW lithium batteries that are maintenance-free, safe, and high-performing is a great way to boost automation efficiency and productivity, whether in manufacturing, warehousing, or logistics operation.



Longer Life
Durable and reliable with up to 10 years design life and 3,500+ cycle life

Zero Maintenance
No water filling, no frequent battery replacements, no acid, and no corrosion



Safe Operation
Equipped with multiple built-in BMS protections for peace of mind

High Performance
Support fast charging and high-power output to meet working needs

Eco-Friendly

Non-toxic, non-polluting, and environmentally friendly.

Specifications

Model	Nominal Voltage	Nominal Capacity	Nominal Energy	Cycle Life	Dimensions (L*W*H)	Weight lbs. (kg)	Continuous Discharge Current	Peak Discharge Current	IP Rating
A2448A	25.6 V	48 Ah	1.228 kWh	>3500 times	11.02 x 7.44 x 6.18 inch (280 x 189 x 157 mm)	35.27 lbs (16 kg)	40 A	50 A 5 s	IP54
A24280A	25.6 V	280 Ah	7.168 kWh	>3500 times	30.71 x 8.27 x 23.03 inch (780 x 210 x 585 mm)	213.85 lbs (97 kg)	120 A	200 A 5 s	IP54
A4852A	48 V	52 Ah	2.496 kWh	>3500 times	13.78 x 11.02 x 5.51 inch (350 x 280 x 140 mm)	41.89 lbs (19 kg)	50 A	75 A 5 s	IP54
S5130A	51.2 V	30 Ah	1.536 kWh	>2000 times	11.81 x 7.87 x 7.28 inch (300 x 200 x 185 mm)	35.71 lbs (16.2 kg)	30 A	60 A 120 s	IP54
S5130B	51.2 V	30 Ah	1.536 kWh	>2000 times	12.99 x 7.87 x 7.15 inch (330 x 200 x 181.5 mm)	28.66 lbs (13 kg)	30 A	60 A 120 s	IP54
A5130A	51.2 V	30 Ah	1.536 kWh	>3500 times	16.06 x 7.36 x 4.84 inch (408 x 187 x 123 mm)	34.17 lbs (15.5 kg)	30 A	60 A 120 s	IP54
A51280A	51.2 V	280 Ah	14.336 kWh	>3500 times	29.84 x 22.05 x 11.02 inch (758 x 560 x 280 mm)	275.58 lbs (125 kg)	240 A	420 A 5 s	IP54
A72120A	73.6 V	119 Ah	8.758 kWh	>2000 times	22.99 x 20.87 x 11.81 inch (584 x 530 x 300 mm)	176.37 lbs (80 kg)	120 A	144 A 5 s	IP54
Working Temperature Range		Charge		Discharge		Storage (1 month)		Storage (1 year)	
		-4°F~131°F (-20°C ~ 55°C)		-4°F~140°F (-20°C ~ 60°C)		-4°F~113°F (-20°C ~ 45°C)		32°F~95°F (0°C~35°C)	

1. All pictures shown are for reference only and data are based on ROYPOW standard test procedures.
2. Actual performance may vary according to local conditions. Only authorized personnel are allowed to operate or make adjustments to the batteries.
3. We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice.

An Unmatched Power with High Compatibility for Multi-shift Applications.

Powerful and reliable, our batteries boost efficiency in material handling. Suitable for applications like logistics, manufacturing, daily goods transporting, etc.



ROYPOW delivers solutions for every brand and size of vehicle, they are generally applied in these famous forklift brands:



Aisle Master	Columbia	Heli	Komatsu	Nissan	TCM
AutoGuide	Combilift	Hoist	Linde	Pack Mule	Toyota
Baoli	Crown	Hubtex	Manitou	Raymond	UniCarriers
Bendi/Landoll	Doosan (Daewoo)	Hyster	Mariotti	Rico	Utilev
Big Joe	Drexel	Hyundai	Mitsubishi	Schreck	White
Blue Giant	Elwell-Parker	Jungheinrich	Motrec	Steinbock	World
Caterpillar	Flexi	Kalmar	Multiton	Taylor-Dunn	Yale
Clark	HC Forklift				

Disclaimer: The information above is intended only to describe that products of ROYPOW are applicable to products of brands above under specific circumstances. It should not be regarded as any illegal use of third-party brands and trademarks. You should not infer that RoyPow has established or has any agency, employment, partnership or joint venture relationship with the companies above.

Which LiFePO₄ Battery is Suitable for Your Forklifts

We make 6 different voltages to cover all classes of equipment.

One Stop for All of Your Battery Needs!

For Class **1** Forklifts

36 V, 48 V, 72 V, 80 V, 90 V Battery Systems

For Counterbalance Forklifts



For Class **2** Forklifts

36 V Battery System

For Order Pickers, Reach Trucks



For Class **3** Forklifts

24 V Battery System



For Pallet Jacks, Stackers, Tugs



LiFePO₄ Batteries for Forklifts

Lithium drop-in replacements for lead-acid batteries.

- ✓ Retrofit your fleet to lithium-ion batteries and keep your equipment running all day long!
- ✓ Power your equipment up to 3 shifts a day!



An Ideal Lithium-ion Solution

Efficient

- ✓ High, consistent performance without the voltage drop at the end of the cycle.
- ✓ Reduce unplanned downtime with fast, efficient, opportunity charging.
- ✓ 10 years design life - a worthwhile upgrade.

Flexible and Worry-free

- ✓ Zero maintenance, no need for water top-ups or electrolyte checks.
- ✓ No battery swapping, reduce related accidents and resulting employee injuries.
- ✓ No need for specific charging room.

Green and Stable

- ✓ No acid spills, no noxious gas emissions.
- ✓ More thermal & chemical stability.
- ✓ Good for you and the planet.

Save Up to
70%
Expenses in 5 Years

Why ROYPOW LiFePO₄ Batteries

5 Year Warranty
5 year warranty brings you hassle-free experience.

Steady Output
LiFePO₄ batteries keep a steady power output, which will not dramatically drop like lead-acid batteries.

Fire Safety
Efficient and eco-friendly, the built-in hot aerosol fire extinguisher can quickly help with the fire fighting and reduce fire hazards for peace of mind.

Heating Function (Optional)
The optional heating function can warm up the battery for optimal charging even at a low temperature of -20 C.

4G Module
For product position tracking, battery health monitoring, and life cycle management.

3,500+ Cycle Life
ROYPOW LiFePO₄ batteries last so long that they outperform traditional batteries.

SoC Meter
Display the battery's state of charge, status and malfunctioning information in real time.

Anti-walking Function
It can prevent your equipment from a sudden start or moving during charging.

Built-in Battery Management System (BMS)
The smart and reliable BMS can ensure a better performance, and deliver longer battery run time and lifespan.

IP65 Protection
Rated at IP65 protection grade, ROYPOW batteries are waterproof and dust-proof to maintain stable performance under all-weather working conditions.



Specifications

Technical Specifications							Charge/Discharge Current			General						
Model	Nominal Voltage	Nominal Capacity	Nominal Energy	Cycle Life	Dimensions (L*W*H)	Weight lbs. (kg)	Charge Current	Continuous Discharge	Maximum Discharge	Casing Material	IP Rating	Certification				
24 V System																
F24100	25.6 V	100 Ah	2.56 kWh	> 3,500 times	25 x 7.09 x 21.2 inch (635 x 180 x 538.5 mm)	110.23 lbs (50 kg)	50 A	100 A	300 A (30 S)	Steel	IP65	/				
F24100M		100 Ah	2.56 kWh		25 x 7.09 x 21.2 inch (635 x 180 x 538.5 mm)	110.23 lbs (50 kg)	50 A	100 A	300 A (30 S)			UL				
F24150		150 Ah	3.84 kWh		25 x 7.09 x 21.2 inch (635 x 180 x 538.5 mm)	132.28 lbs (60 kg)	50 A	100 A	300 A (30 S)			/				
F24150L		150 Ah	3.84 kWh		25 x 7.09 x 21.2 inch (635 x 180 x 538.5 mm)	132.28 lbs (60 kg)	50 A	100 A	300 A (30 S)			UL				
F24160		160 Ah	4.10 kWh		24.57 x 8.27 x 24.69 inch (624 x 210 x 627 mm)	198.42 lbs (90 kg)	80 A	160 A	480 A (30 S)			/				
F24200		200 Ah	2.69 kWh		28.35 x 8.27 x 24.80 inch (720 x 210 x 630 mm)	507 lbs (230 kg)	100 A	200 A	600A (30 S)			/				
F24230		210 Ah	5.38 kWh		24.57 x 11.18 x 24.69 inch (624 x 284 x 627 mm)	220.46 lbs (100 kg)	115 A	230 A	600 A (30 S)			/				
F24280		280 Ah	7.17 kWh		24.57 x 8.27 x 24.69 inch (624 x 210 x 627 mm)	242.5 lbs (110 kg)	140 A	280 A	600 A (30 S)			/				
F24320		320 Ah	8.06 kWh		25.59 x 13.78 x 18.50 inch (650 x 350 x 470 mm)	286.60 lbs (130 kg)	160 A	315 A	600 A (30 S)			/				
F24400		400 Ah	10.24 kWh		28.34 x 8.27 x 24.80 inch (720*210*630)	286.60 lbs (260 kg)	200 A	400 A	600 A (30 S)			/				
F24420		420 Ah	10.75 kWh		30.94 x 8.27 x 24.80 inch (786 x 210 x 630 mm)	485 lbs (220 kg)	200 A	420 A	600 A (30 S)			/				
F24560		560 Ah	14.34 kWh		30.71 x 16.73 x 18.50 inch (780 x 425 x 470 mm)	848.8 lbs (385 kg)	200 A	560 A	700 A (30 S)			/				
F24560L		560 Ah	14.34 kWh		36.67x 12.8 x 22.48 inch (779 x 325 x 571 mm)	848.8 lbs (385 kg)	200 A	350 A	500 A (30 S)			UL				
F24690		690 Ah	17.66 kWh		35.83x 12.6 x 31.89 inch (910 x 320 x 810mm)	1860 lbs (844 kg)	200 A	560 A	700 A (30 S)			/				
F24840		840 Ah	21.50 kWh		38.80x 14.25 x 31 inch (985.5x 361.9 x 787.4mm)	1567 lbs (711 kg)	200 A	560 A	700 A (30 S)			/				
36 V System																
F36420	38.4 V	420 Ah	16.13 kWh	> 3,500 times	31.50 x 3.78 x 22.44 inch (800 x 350 x 570 mm)	617.29 lbs (280 kg)	200 A	420 A	700 A (30 S)	Steel	IP65	/				
F36460		460 Ah	17.66 kWh		30.71 x 16.73 x 22.44 inch (750 x 425 x 570 mm)	617.29 lbs (280 kg)	200 A	420 A	700 A (30 S)			/				
F36560		560 Ah	21.50 kWh		32.87x 16.73 x 22.44 inch (835 x 425 x 570 mm)	617.29 lbs (250 kg)	200 A	420 A	700 A (30 S)			/				
		560 Ah	21.50 kWh		31.50 x 29.92 x 13.78 inch (800 x 760 x 350 mm)	551.16 lbs (250 kg)	200 A	420 A	700 A (30 S)			/				
F36608		608 Ah	23.35 kWh		30.71 x 16.73 x 22.44 inch (780 x 425 x 570 mm)	617.29 lbs (280 kg)	200 A	420 A	700 A (30 S)			/				
		608 Ah	23.35 kWh		31.50 x 24.61 x 16.54 inch (800 x 625 x 420 mm)	551.16 lbs (250 kg)	200 A	420 A	700 A (30 S)			/				
F36690AJ		690 Ah	26.50 kWh		35.43 x 16.73 x 22.44 inch (900 x 425 x 570 mm)	683.43 lbs (310 kg)	200 A	420 A	700 A (30 S)			UL				
F36690BC		690 Ah	26.50 kWh		38.19x 20.39 x 29.49 inch (970 x 518 x 749 mm)	2705.07 lbs (1227kg)	200 A	420 A	700 A (30 S)			UL				
F36840		840 Ah	32.26 kWh		34.64 x 29.92 x 18.11 inch (880 x 760 x 460 mm)	718.70 lbs (326 kg)	200 A	420 A	700 A (30 S)			/				
		840 Ah	32.26 kWh		33.46 x 24.01 x 22.44 inch (850 x 610 x 570 mm)	749.57 lbs (340 kg)	200 A	420 A	700 A (30 S)			/				
		840 Ah	32.26 kWh		33.46 x 16.93 x 28.34 inch (850 x 430 x 720 mm)	870.83 lbs (395 kg)	200 A	420 A	700 A (30 S)			/				
		840 Ah	32.26 kWh		35.43 x 31.49 x 18.50 inch (900 x 800 x 470 mm)	683.43 lbs (310 kg)	200 A	420 A	700 A (30 S)			/				
48 V System																
F48210		51.2 V	210 Ah		10.75 kWh	> 3,500 times	31.50 x 14.37 x 16.14 inch (800 x 365 x 410 mm)	297.62 lbs (135 kg)	105 A			210 A	500 A (30 S)	Steel	IP65	/
F48230			230 Ah		11.78 kWh		38 x 11.81 x 21.65 inch (965 x 300 x 550mm)	815.71 lbs (370 kg)	200 A			350 A	500 A (30 S)			/
F48280	280 Ah		14.33 kWh	30.71 x 16.73 x 18.50 inch (780 x 425 x 470 mm)	396.83 lbs (180 kg)		140 A	280 A	500 A (30 S)	/						
F48315	315 Ah		16.1 kWh	27.56 x 22.05 x 18.11 inch (700 x 560 x 460 mm)	507.06 lbs (230 kg)		157 A	350 A	500 A (30 S)	/						
	315 Ah		16.1 kWh	31.5 x 13.78 x 22.44 inch (800 x 350 x 570 mm)	617 lbs (280 kg)		157 A	350 A	500 A (30 S)	/						
F48420AG	420 Ah		21.50 kWh	37.40 x 13.78 x 22.44 inch (950 x 350 x 570 mm)	661.39 lbs (300 kg)		200 A	350 A	700 A (30 S)	UL						
F48420CA	420 Ah		21.50 kWh	37.40 x 24.8 x 22.5 inch (970 x 630 x 571.5 mm)	661.39 lbs (300 kg)		200 A	350 A	700 A (30 S)	UL						
F48420BE	420 Ah		21.50 kWh	31.50 x 24.02 x 18.11 inch (800 x 610 x 460 mm)	617.29 lbs (280 kg)		200 A	350 A	700 A (30 S)	/						
F48460	460 Ah		23.55 kWh	32.28 x 25.50 x 18.50 inch (820 x 650 x 470 mm)	639.34 lbs (290 kg)		200 A	350 A	700 A (30 S)	/						
	460 Ah		23.55 kWh	31.50 x 16.73 x 22.44 inch (800 x 425 x 570 mm)	650.36 lbs (295 kg)		200 A	350 A	700 A (30 S)	/						

Specifications

Technical Specifications							Charge/Discharge Current			General						
Model	Nominal Voltage	Nominal Capacity	Nominal Energy	Cycle Life	Dimensions (L*W*H)	Weight lbs. (kg)	Charge Current	Continuous Discharge	Maximum Discharge	Casing Material	IP Rating	Certification				
48 V System																
F48560AY	51.2 V	560 Ah	28.67 kWh	> 3,500 times	32.28 x 30.71 x 18.11 inch (820 x 780 x 460 mm)	683.43 lbs (310 kg)	200 A	350 A	700 A (30 S)	Steel	IP65	/				
F48560		560 Ah	28.67 kWh		35.43 x 31.89 x 13.78 inch (900 x 810 x 350 mm)	683.43 lbs (310 kg)	200 A	350 A	700 A (30 S)			/				
F48560X		560 Ah	28.67 kWh		35.43 x 16.73 x 22.44 inch (900 x 425 x 570 mm)	771.62 lbs (350 kg)	200 A	350 A	700 A (30 S)			UL				
F48560BS		560 Ah	28.67 kWh		35.43 x 16.73 x 22.44 inch (970 x 831 x 571.5 mm)	3199 lbs (1451 kg)	200 A	350 A	700 A (30 S)			UL				
F48690W		690 Ah	35.33 kWh		37.80 x 16.73 x 22.83 inch (960 x 425 x 580 mm)	837.76 lbs (380 kg)	200 A	350 A	700 A (30 S)			UL				
F48690BD		690 Ah	35.33 kWh		35.43 x 16.73 x 22.44 inch (970 x 831 x 571.5 mm)	3199 lbs (1451 kg)	200 A	500 A	700 A (30 S)			UL				
F48690U		690 Ah	35.33 kWh		34.65 x 29.92 x 18.50 inch (880 x 760 x 470 mm)	749.57 lbs (340 kg)	200 A	500 A	700 A (30 S)			/				
F48840		840 Ah	43 kWh		34.84 x 32.68 x 18.50 inch (885 x 830 x 570 mm)	529.1 lbs (240 kg)	200 A	500 A	700 A (30 S)			/				
		840 Ah	43 kWh		32.28 x 24.8 x 22.44 inch (820 x 630 x 570 mm)	1135 lbs (515 kg)	200 A	500 A	700 A (30 S)			/				
F481120		1120 Ah	57.34 kWh		39.37 x 31.50 x 22.24 inch (1000 x 800 x 565 mm)	1256 lbs (570 kg)	200 A	500 A	700 A (30 S)			/				
72 V System																
F72420		73.6 V	420 Ah		30.9 kWh	> 3,500 times	31.50 x 14.57 x 22.44 inch (800 x 370 x 570 mm)	903.90 lbs (410 kg)	200 A			350 A	700 A (30 S)	Steel	IP65	/
F72460			460 Ah		33.86 kWh		27.56 x 16.73 x 22.44 inch (700 x 425 x 570 mm)	925.94 lbs (420 kg)	200 A			350 A	700 A (30 S)			/
			460 Ah		33.86 kWh		25.59 x 24.80 x 18.50 inch (650 x 630 x 470 mm)	947.99 lbs (430 kg)	200 A			350 A	700 A (30 S)			/
F72560			560 Ah		41.22 kWh		29.92 x 16.73 x 22.44 inch (760 x 425 x 570 mm)	1102.31 lbs (500 kg)	200 A			350 A	700 A (30 S)			/
	560 Ah		41.22 kWh	30.71 x 24.80 x 18.50 inch (780 x 630 x 470 mm)	1124.36 lbs (510 kg)		200 A	350 A	700 A (30 S)	/						
80 V System																
F80280	80 V	280 Ah	22.4 kWh	> 3,500 times	35.43 x 16.73 x 22.44 inch (900 x 425 x 570 mm)	661.38 lbs (300 kg)	200 A	300 A	500 A (30 S)	Steel	IP65	/				
F80400		400 Ah	32.0 kWh		35.43 x 22 x 22.44 inch (900 x 560 x 570 mm)	925.95 lbs (420 kg)	200 A	300 A	700 A (30 S)			/				
F80420G/ F80420H		420 Ah	33.6 kWh		35.43 x 24.80 x 22.44 inch (900 x 630 x 570 mm)	881.85 lbs (400 kg)	200 A	350 A	700 A (30 S)			/				
		F80460H/F80460G F80460I/F80460J	460 Ah		36.8 kWh	32.28 x 24.61 x 22.83 inch (820 x 625 x 580 mm)	881.85 lbs (400 kg)	200 A	350 A			700 A (30 S)	/			
F80560		560 Ah	44.8 kWh		32.28 x 27.17 x 22.44 inch (820 x 690 x 570 mm)	1058.22 lbs (480 kg)	200 A	350 A	700 A (30 S)			/				
		560 Ah	44.8 kWh		31.89 x 28.74 x 22.44 inch (810 x 730 x 570 mm)	1080.27 lbs (490 kg)	200 A	350 A	700 A (30 S)			/				
F80608		608 Ah	48.64 kWh		35.43 x 31.89 x 22.44 inch (900 x 810 x 570 mm)	1102.31 lbs (500 kg)	200 A	420 A	700 A (30 S)			/				
F80690		690 Ah	55.2 kWh		38.58 x 31.89 x 22.44 inch (980 x 810 x 570 mm)	1025.15 lbs (465 kg)	200 A	420 A	700 A (30 S)			/				
F80690D		690 Ah	55.2 kWh		31.89 x 30.71 x 22.44 inch (810 x 780 x 570 mm)	1201.52 lbs (545 kg)	200 A	420 A	700 A (30 S)			UL				
F80690K		690 Ah	55.2 kWh		39.72 x 32.76x 29.49 inch (1009 x 832 x 749 mm)	2705 lbs (1227 kg)	200 A	420 A	700 A (30 S)			UL				
F80840		840 Ah	67.2 kWh		39.37 x 32.28 x 22.44 inch (1000 x 820 x 570 mm)	1444.03 lbs (655 kg)	200 A	420 A	700 A (30 S)			/				
90 V System																
F90460		89.6 V	460 Ah		41.2 kWh	> 3,500 times	39.37 x 24.41 x 23.62 inch (1000 x 620 x 600 mm)	1135.38 lbs (515 kg)	200 A			350 A	700 A (30 S)	Steel	IP65	/
F90608			608 Ah		54.48 kWh		35.43 x 27.17 x 22.44 inch (900 x 690 x 570 mm)	1212.54 lbs (550 kg)	200 A			200 A	700 A (30 S)			/
96 V System																
F961120A	96 V	1120 Ah	107.52 kWh	> 3,500 times	55.90 x 24.21 x 30.9 inch (1420 x 615 x 785 mm A/B BOX)	9038.95 lbs (4100 kg)	200 A	350 A	700 A (30 S)	Steel	IP65	/				
F961120B		1120 Ah	107.52 kWh		47.83 x 28.15 x 30.51 inch (1215 x 715 x 775 mm)	8950.77 lbs (4060 kg)	200 A	350 A	700 A (30 S)			/				
Working Temperature Range							Charge		Discharge		Storage (1 month)		Storage (1 year)			
							-4°F~-131°F (-20°C ~ 55°C)		-4°F~-131°F (-20°C ~ 55°C)		-4°F~-131°F (-20°C ~ 55°C)		32°F~95°F (0°C~35°C)			

1. All pictures shown are for reference only and data are based on ROYPOW standard test procedures.
 2. Actual performance may vary according to local conditions. Only authorized personnel are allowed to operate or make adjustments to the batteries.
 3. We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice.



IP67 $-40^{\circ}\text{C} \sim -20^{\circ}\text{C}$ Anti-Freeze Lithium Battery for Forklifts

Power through the breeze.
Unstoppable energy for your forklift in the cold.



Waterproof Cable Glands

- Less Capacity Loss
- Uncompromising Charging Efficiency
- Eco-friendliness



IP67 Ingress Protection
External waterproof cable glands with seal rings for superior water tightness



On-Board Thermal Insulation
Covered with quality thermal insulation design to avoid capacity loss



Anti-Condensation Design
Effective water absorption designs keep the inside battery box dry



Pre-Heating Function
Warm the battery for optimal charging even at a low temperature



Intelligent BMS
Designed for peak efficiency, intelligent management and safe protections



Opportunity Charging and Fast Charging
Can recharge in a short break to deal with multi-shift operations



Lasts Longer
Have up to 10 years of lifespan. Withstand up to 3,500 cycles



Zero Maintenance
No need for water top-ups or electrolyte checks. No frequent battery swaps.



Applications

Many products require constant refrigeration. Medicines, Food, Meat, Fruits, Vegetables, Dairy, and beverages require cold transportation as well as cold storage. For material handling in such cold storage warehouses,

ROYPOW cold storage lithium-ion battery solution is the best choice.



Cold Storage Battery System Specification:

Rated Voltages:
24 V, 36 V, 48 V, 72 V, 80 V, 96 V

Discharging temperature range:
 -20°C to $+55^{\circ}\text{C}$

Available battery system energy content:
2.56 kWh-116 kWh

Cold storage temperature range:
 -40°C to $+55^{\circ}\text{C}$

Charger Specification:

Rated Voltages:
24 V, 36 V, 48 V, 72 V, 80 V, 96 V

Working temperature range:
 -20°C to $+50^{\circ}\text{C}$

Input:
220V AC single phase or 400V AC three phase

Working humidity:
0%-95%RH

Available charging current:
50A to 400A

NOTE: Charger need to be placed outside cold storage warehouse.



Reliable Power for Most Aerial Lift Brands

ROYPOW lithium-ion batteries deliver consistent, reliable power for Aerial Lifts.



Advanced battery solution for most leading brands of aerial work platforms. They can be generally applied in these famous aerial work platform brands:

- | | | | |
|----------------|----------|----------|-----------|
| Zoomlion | Genie | Mantall | Noble |
| Xcmg | JLG | Runshare | Eastmanhm |
| Dingli | Sunward | Skyjack | Airman |
| LGMG | Sany | Manitou | Sivge |
| Sinoboom | Haulotte | Emis | More> |
| Snorkel/Xtreme | LiuGong | | |

Disclaimer: The information above is intended only to describe that products of ROYPOW are applicable to products of brands above under specific circumstances. It should not be regarded as any illegal use of third-party brands and trademarks. You should not infer that RoyPow has established or has any agency, employment, partnership or joint venture relationship with the companies above.

Which LiFePO₄ Battery is Suitable for Your Aerial Work Platforms?

One Stop for All of Your Battery Needs!

We make 24 and 48 volt systems to cover small and large platform Electric Scissor Lifts:

Small-platform

24 V Battery System

For small-platform electric scissor lifts



Large-platform

48 V Battery System



For large-platform electric scissor lifts



LiFePO₄ Batteries for Aerial Work Platforms

Switch to new technology, lithium drop-in replacements for lead-acid batteries.

- ✓ A full range of lithium-ion battery to power your aerial lifts.
- ✓ Maximum uptime and flexible lifting.



An Ideal Lithium-ion Solution

Efficient

- ✓ High, consistent performance without the voltage drop at the end of the cycle.
- ✓ Reduce unplanned downtime with fast, efficient, opportunity charging.
- ✓ 10 years design life - a worthwhile upgrade.

Flexible and Worry-free

- ✓ Zero maintenance, no need for water top-ups or electrolyte checks.
- ✓ No battery swapping, reduce related accidents and resulting employee injuries.
- ✓ No need for specific charging room.

Green and Stable

- ✓ No acid spills, no noxious gas emissions.
- ✓ More thermal & chemical stability.
- ✓ Good for you and the planet.



Why ROYPOW LiFePO₄ Batteries

5 Year Warranty
5 year warranty and timely technical support.



Key Features

Steady Output

LiFePO₄ batteries keep a very steady power output. They are suitable for applications.



Long Life

3,500+ cycle life outperforms traditional batteries.





Heating Function (Optional)

Heating function to warm up the battery at a low temperature for charging and discharging.



Intelligent BMS

All-time cell balancing and multiple built-in protections, including short circuit protection, high temperature protection, high voltage protection and so on to get better performance and longer life.



Specifications



Model	Technical Specifications				Dimensions (L*W*H)	Weight lbs. (kg)	Discharge Current		General	
	Nominal Voltage	Nominal Capacity	Stored Energy	Cycle Life			Continuous Discharge	Maximum Discharge	Casing Material	IP Rating
24 V System										
T24100L	25.6 V	100 Ah	2.56 kWh	>3,500 times	13.8×9.8×10.3 inch (350×250×262 mm)	56 lbs. (25.6 kg)	150 A	250 A (30 S)	Steel	IP67
T24150L		150 Ah	3.84 kWh		20.3×10.1×10.3 inch (517×257×262 mm)	77 lbs. (35 kg)	150 A	350 A (30 S)	Steel	IP67
T24200L		200 Ah	5.12 kWh		19.2×13.4×10.5 inch (488×340×267 mm)	101 lbs. (46 kg)	150 A	350 A (30 S)	Steel	IP67
T24230L		230 Ah	5.89 kWh		16.53×14.33×10.51 inch (420×364×267 mm)	105.82 lbs. (48 kg)	200 A	350 A (30 S)	Steel	IP67
T24280L		280 Ah	7.17 kWh		17.05×16.53×10.51 inch (433×420×267 mm)	121.25 lbs. (55 kg)	200 A	350 A (30 S)	Steel	IP67
48 V System										
T51230P	51.2V	230 Ah	11.78 kWh	>3,500 times	23.4×11.69×10.9 inch(A/B BOX) (597×297×277 mm A/B BOX)	220 lbs. (100 kg)	230 A	350 A (30 S)	Steel	IP67
T51280P		280 Ah	14.34 kWh		28.0×10.8×10.8 inch(A/B BOX) (712×275×275 mm A/B BOX)	243 lbs. (110 kg)	280 A	350 A (30 S)	Steel	IP67
Working Temperature Range		Charge		Discharge		Storage (1 month)		Storage (1 year)		
		-4°F~131°F (-20°C ~ 55°C)		-4°F~131°F (-20°C ~ 55°C)		-4°F~131°F (-20°C ~ 55°C)		32°F~95°F (0°C~35°C)		

1. All pictures shown are for reference only and data are based on ROYPOW standard test procedures.

2. Actual performance may vary according to local conditions. Only authorized personnel are allowed to operate or make adjustments to the batteries.

3. We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice.

Ideal Power for the Top Brands

ROYPOW lithium batteries are more reliable and will provide unmatched power for many floor cleaning machines.



Ideal battery solutions for most leading brands of floor cleaning machines. They can be generally applied in these famous floor cleaning machine brands:

Nilfisk/Advance
Tennant
Nilfisk
Hako
Kärcher

IPC
Comac
FIMAP
Dulevo
TVX

Viper
Clarke
ICE
NSS
Minuteman

PowerBoss
Eureka
Betco
More>

Disclaimer: The information above is intended only to describe that products of ROYPOW are applicable to products of brands above under specific circumstances. It should not be regarded as any illegal use of third-party brands and trademarks. You should not infer that RoyPow has established or has any agency, employment, partnership or joint venture relationship with the companies above.

Which LiFePO₄ Battery is Suitable for Your Floor Cleaning Machines?

One Stop for All of Your Battery Needs!

We make 24 and 36 volt systems to cover most Floor Cleaning Machines.

24 V Battery System

For Walk Behind Sweepers & Scrubbers



36 V Battery System

For Ride-On Sweepers and Scrubbers



LiFePO₄ Batteries for Floor Cleaning Machines

Switch to new technology, lithium drop-in replacements for lead-acid batteries.

- ✓ Superior performance from these safe, durable batteries.
- ✓ Keep your machines always ready to go!



More Time Cleaning, Less Time Worrying

Flexible and Worry-free

- ✓ Much lighter than the traditional battery.
- ✓ No frequent battery swapping.
- ✓ No Memory Effect, opportunity charge anytime.

Stable and Sustained

- ✓ No acid spills, no noxious gas emissions.
- ✓ More thermal & chemical stability.
- ✓ High consistent performance without sudden power sag.

A Good Investment

- ✓ Zero maintenance, to save labor and maintenance costs.
- ✓ Reduce unplanned downtime with fast, efficient, opportunity charging.
- ✓ No battery swapping, reduce related accidents and resulting employee injuries.
- ✓ Up to 10 years design life reduces overall battery investment.

Save Up to
70%
Expenses in 5 Years

Why ROYPOW LiFePO₄ Batteries



5 Year Warranty

5 year warranty and timely technical support.



Steady Output

LiFePO₄ batteries keep a very steady power output. They are intended for applications.



Key Features

Heating Function (Optional)

Heating function to warm up the battery at a low temperature for charging and discharging.




Long Life

3,500+ cycle life outperforms traditional batteries.



Intelligent BMS

All-time cell balancing and multiple built-in protections, including short circuit protection, high temperature protection, high voltage protection and so on to get better performance and longer life.



Specifications


Model	Nominal Voltage	Nominal Capacity	Technical Specifications			Dimensions (L*W*H)	Weight lbs. (kg)	Discharge Current		General	
			Stored Energy	Cycle Life				Continuous Discharge	Maximum Discharge	Casing Material	IP Rating
24 V System											
S2460A	25.6 V	60 Ah	1.54 kWh	>3,500 times	12.1x6.6x8.9 inch (307x168x226 mm)		33 lbs. (15 kg)	60 A	200 A (30 S)	ABS	IP65
S2460D		60 Ah	1.54 kWh		11.42x9.65x9.84 inch (290x245x250 mm)		46.30 lbs. (21 kg)	65 A	200 A (30 S)	Steel	IP67
S24100C		100 Ah	2.56 kWh		13.31x12.09x9.16 inch (338x307x232.7 mm)		63.49 lbs. (28.8 kg)	100 A	250 A (30 S)	Steel	IP67
S24150A		150 Ah	3.84 kWh		15.75x12.99x10.24 inch (440x330x260 mm)		85.5 lbs. (38.8 kg)	150 A	250 A (30 S)	Steel	IP67
W24200A		200 Ah	5.12 kWh		19.2x13.8x10.80 inch (488x350x274.3 mm)		101.41 lbs. (46 kg)	150 A	250 A (30 S)	Steel	IP67
W24230L		230 Ah	5.89 kWh		16.5x14.33x10.51 inch (420x364x267 mm)		101 lbs. (46 kg)	150 A	250 A (30 S)	Steel	IP67
W24280L		280 Ah	7.17 kWh		17.05x16.53x10.51 inch (433x420x267 mm)		121.25 lbs. (55 kg)	150 A	250 A (30 S)	Steel	IP67
W24314L		314 Ah	8.04 kWh		28.0x10.51x10.51 inch (433x420x267 mm)		127.87 lbs. (58 kg)	150 A	250 A (30 S)	Steel	IP67
36 V System											
S38100A	38.4 V	100 Ah	3.84 kWh	>3,500 times	15.34 x 10.83 x 10.63 inch (389.6 x 275.1 x 270 mm)		94.80±4.41 lbs (43±2 kg)	150 A	250 A (30 S)	Steel	IP67
S38150A		150 Ah	5.76 kWh		20.47x16.14x8.91 inch (520x410x226.2 mm)		127.87 lbs. (58 kg)	150 A	250 A (30 S)	Steel	IP67
W38200A		200 Ah	7.68 kWh		22.60x19.68x12.51 inch (574x500x317.9 mm)		136.68 lbs. (62 kg)	150 A	250 A (30 S)	Steel	IP67
S38230L		230 Ah	8.83 kWh		23.62x13.78x10.80 inch (600x350x274.3 mm)		142.86 lbs. (64.8 kg)	150 A	250 A (30 S)	Steel	IP67
W38280L		280 Ah	10.75 kWh		22.61x19.69x12.52 inch (574.3x500x317.9 mm)		217.34 lbs. (95 kg)	150 A	250 A (30 S)	Steel	IP67
W38314L		314 Ah	12.06 kWh		22.61x19.69x12.52 inch (574.3x500x317.9 mm)		209.44 lbs. (98.6 kg)	150 A	250 A (30 S)	Steel	IP67
Working Temperature Range		Charge		Discharge		Storage (1 month)		Storage (1 year)			
		-4°F~131°F (-20°C ~ 55°C)		-4°F~131°F (-20°C ~ 55°C)		-4°F~131°F (-20°C ~ 55°C)		32°F~95°F (0°C~35°C)			

1. All pictures shown are for reference only and data are based on ROYPOW standard test procedures.
2. Actual performance may vary according to local conditions. Only authorized personnel are allowed to operate or make adjustments to the batteries.
3. We reserve the right to make revisions as well as product alterations and improvements at any time without prior notice.

More about ROYPOW Lithium-ion Batteries



Quality and safety always come first. We also offer intelligent design from our professional R&D team.



Intelligent Design

- Built-in BMS**
 For cell balancing and advanced battery management.
- Control Panel Included**
 Showing all critical battery functions in real time, voltage, current, and remaining charging time and fault alarm.
- Battery Pack Module**
 Using LiFePO₄ cells to insure stable and safe battery performance.

Battery Management System (BMS)

The built-in BMS is equipped with automotive-grade components assuring safety, top quality and high energy density to provide a fully optimized solution for demanding industrial applications.

BMS software ensures the battery provides peak performance when in operation, delivers longer run time between charges, maximizes the total battery lifespan and to communicate well between the charger, battery and users.



The BMS can offer:

All-time Cell Balancing and Battery Management.

Through the intelligent balancing strategy, balancing between individual cells can be realized. The BMS can keep the battery's consistency at all times when in operation, maximizing the battery efficiency and improving the battery's working life.

Battery Real-time Monitoring and Communication Through CAN.

Monitoring cell voltage, electric current and battery temperature so that any movement outside the normal range disconnects the cell or the entire battery.

Fault Alarm and Safety Protection.

When the battery is less than 10%, it will beep to prompt for charging in case of stopping somewhere far away from the charge station suddenly without notice. Over/under voltage, low/over temperature, over current or other faults will prompt to make the battery safe. Safety always comes first.


4G Module (for Forklift Batteries)



ROYPOW smart 4G module offers remote monitoring in real time, even in different countries. If faults occur, you can get an alarm. If the faults cannot be solved in person, you can get a remote diagnosis online from us to solve the problems as soon as possible.

With OTA (over the air) connectivity, remote software upgrades can solve software many problems in time and remote GPS can lock the forklift automatically if necessary.

Smart On-line Cloud Platform



It provides integrated battery system management information, including battery quantities, real-time data and status, positions and trajectories, alarm record, etc. One phone or one computer can monitor all the batteries, no matter where you are, very easy and convenient to manage.

Original Chargers for Forklift

ROYPOW professional charger enables optimal battery performance and the best communication between the charger and the battery.



Intelligent Charging Management

To use the ROYPOW charger, the battery management system (BMS) can control the charging current according to different temperatures and SOC of the batteries.

ROYPOW's intelligent BMS ensures the safety of the battery and improves the charging efficiency.


When the battery is at a low voltage, the battery can be charged at low current to ensure battery safety.

When the battery is less than 10%, it will beep to prompt for charging.

Over-temperature protection	Short-circuit protection	Anti-reverse connection function	Over-charge protection
Smart display	Current limit function	Automatic power off	Over-current protection
Over-voltage protection	Timing protection	Wide voltage operation	Constant current constant voltage

How to Charge? Easy and safe

i During the charging process, power to the lift is disconnected to prevent drive off.



Smart Display

Once the charger is connected, it will show the battery status, and the operator can leave the truck between shifts and have a rest.



Where do ROYPOW lithium-ion batteries charge? Flexible

- ✓ The batteries can be charged in the truck. No frequent battery swaps or battery storage room are required.
- ✓ The charging stations can be located anywhere in the facility that will promote proper charging by the operator. Eliminate charging room and related ventilation equipment.

TIPS

Compare to the charging location for lead-acid batteries:

Lead-acid batteries need extra batteries and battery storage room for swapping. And they also need a specific charging room with a ventilation system to avoid noxious gas when charging.